

versamill 5X-300D

small-format industrial-quality machines.

The entry into our Versamill compact-machine lineup is our Versamill 5X-300D precision dental machining center. The 5X-300D not only masters conventional crown and bridge work but is also designed for fabricating more complex indications with dry millable materials.

With the versamill 5X-300D you get a complete, industrial-quality manufacturing solution used by dental laboratories and milling centers around the world that is specifically designed to meet the demanding support requirements of these dental laboratories & milling centers.



INDICATIONS

- Inlays, onlays, copings, crowns, veneers, splints & guides.
- Removable & fixed bridges, models, hybrid abutments & zirconia bars (with optional modules).
- Process PMMA, zirconia, PEEK composites, resins, Pekkton, and more.



SPEED WITHOUT SACRIFICE

The strength and rigidity of the Versamill 5X-300D coupled with the undercut machining capability of full 5-Axis control provides perfect fits, great anatomical detail and the best possible restorative margins with faster cycle times and greater tool life.

- Single-unit zirconia crowns in less than 14 minutes.
- Single-unit PMMA crowns in as little as 15 minutes.
- 6-implant zirconia implant bridges in less than 105 minutes.

RIGID CONSTRUCTION

- Cast and heavy fabricated aluminum-plate frame.
- Zero-stack tolerance, 5-axis trunnion.
- Liner guides & ballscrews with preloaded bearings.
- Closed loop system with micro-stepper technology and position encoders.





Clean Operation.
Class-leading .5kW spindle with vacuum shroud that assures efficient removal of machining by-products from the machining area.



Heavy-gage aluminum fabricated frame provides the rigidity required to absorb vibration and dissipate heat.



5-axis operation with quick-change universal fixture.
Rotary axis trunnion driven by high-torque reduction gears with fully supported zero stack tolerance quick-change part holding fixture.



12-station ATC houses sturdy, flex-resisting 4.0mm diameter cutting tools.
The spacious work area of the Versamill makes for easy operation and part handling.



Use of precision ball screws with anti-backlash ball nuts along with linear guides and closed-loop servo drives assures superior dynamic motion and positional accuracy.



Powerful, High-speed Precision Spindle.
Class-leading, 80,000 rpm, .5kW spindle delivers up to 8.4Nm torque.



Quick-change 6-unit CAD-block cartridge.
Facilitates production of Nano-composite (Vericom Mazic® duro, Lava Ultimate® etc.), and other pre-mounted dental materials.




Optional Heavy-duty Machine Stand.
Provides stability, storage and mobility to meet your ever-changing environmental needs.



CAM SOFTWARE: PROVEN & FULL-FEATURED

The versamill 5X-300D is powered by hyperDENT CAM software from FOLLOW-ME! Technology Group.

hyperDENT incorporates efficient proven milling cycles from the industrial segment to provide maximum process stability and indication quality, including patent-protected milling strategies used for complex materials ensuring perfect surface quality while maximizing tool life.



hyperDENT
COMPACT

OPTIONAL MODULES

Full Denture, Template Generator

As with our Versamill machine technology, we leverage our 40 years of digital design and manufacturing experience - spanning all market segments including the dental industry - to provide additional software enhancements over and above a vendors' standard deliverable product. These unique enhancements, which are not available from any other supplier, provide additional functionality, while assuring unrivaled reliability and increased productivity.

Versamill 5X-300D Specifications

Number of axes:		5 simultaneous
Travel (x, y, z axis):	(mm)	145 x 110 x 85
A Rotational axis:	(degrees)	360 °
B Rotational axis:	(degrees)	±30°
Drive Mechanism:		Ball screw
Way System:		Linear Guide
Repeatability:	(µm)	±5.0
Spindle Power:	(watts)	AC 0.5kW max
Spindle Speed:	(rpm)	6,000 - 80,000
ATC number of tools:	4.0mm Ø	12
Axis Drive System	Closed-Loop	Micro-stepper w/Encoder
Blank disc diameter:	(mm)	98 Ø
Machine size (W x H x L):	(mm)	540 x 580 x 630
Table size (W x H x L):	(mm)	540 x 580 x 950
Weight:	(Kg)	90Kg
Input Power	(VAC/50-60Hz)	100 - 240 Single Phase